

pro'wood
KILN DRIED

STRAIGHT
TO THE POINT.

KILN DRIED

NEVER SETTLE.

DRY. STABLE.

READY TO SEAL.



**KILN DRIED AFTER TREATMENT (KDAT)
FOR STABILITY AND FAST RESULTS.**

In the kiln, treated wood is spaced evenly and exposed to the exact temperature for removing excess moisture. This allows you to complete your job immediately, rather than waiting weeks or months to experience the satisfaction of a finished project.

SEE HOW WE STACK UP
[PROWOODLUMBER.COM/KDAT](https://prowoodlumber.com/KDAT)





pro'wood
KILN DRIED

STAIN- OR SEAL- READY PROJECTS.



Avoid waiting for wet-treated wood to dry naturally. Kiln dried, pressure-treated wood can be sealed immediately.

MINIMAL SHRINK & LIGHTWEIGHT.



Drying increases wood's strength while reducing its weight, making it easier to transport, handle and cut. Experience more accurate measurements when building with KDAT.

WE RECOMMEND:

- ❑ Keep material dry before and during installation if possible.
- ❑ Use deck screws. Pre-drill close to the ends of the deck boards.
- ❑ KDAT decking should be gapped the width of an 8 penny nail (1/8"). This gap will allow for the normal expansion and contraction of the product.



PROWOOD KDAT IS BUILDING CODE COMPLIANT AND BACKED WITH A LIFETIME LIMITED WARRANTY.



PROWOODLUMBER.COM
FIND A DEALER NEAR YOU

DECKING | FENCING | RAILING | TIMBERS



We've made a commitment to the environment. And to you.

Our products are safe — even for children and pets — when used in accordance with our Safety Data Sheet (SDS).

ProWoodLumber.com/SDS



IBC and IRC code complaint ProWood treated products are available treated to AWPA U1 standards. ProWood is a registered trademark of UFP Industries, Inc. The Home Innovation NCBS Green Certified logo is a certification trademark of the National Association of Home Builders. Greenguard and the Greenguard logo are registered trademarks of Air Quality Sciences, Inc.
© 2022 UFP Retail Solutions, LLC. All rights reserved. 14125_03/22

NEVER SETTLE.