

WHY PROWOOD FR?

- Developed by UFP Industries and is UL Solutions-tested to their highest category designation of FR-S, signifying minimal flame-spread and smoke development
- Greenguard Gold certification for low emissions
- Backed by a 50-Year Limited Warranty against structural failure
- Verified by certified engineers according to the latest and most stringent versions of ASTM strength durability standards
- Kiln Dried to reduce shrinkage
- Full BIM catalog and 3-part specification to allow great ease when specifying

BACKER BLOCK

These precut blocks are used to support installation of interior cabinets, vanities, shelving, grab rails, trim and more. And because they're made from ProWood FR pressure treated dimensional lumber, the holding strength is much greater than plywood.





DIMENSIONAL LUMBER

ProWood® FR fire-retardant-treated wood has a Class A Flame Spread Index of 25 or less, the best possible rating awarded to fire-retardant building products. Flame spread rating was achieved through ASTM E84 30-minute test. ProWood FR pressure-treated lumber and plywood have also been tested by independent accredited laboratories, following industry standards ASTM D5564 and ASTM D5516, to develop strength design factors for various use conditions.



1-HR WALL PANEL

ASTM E119 Tested, the 1-hour wall assembly is load bearing rated from one side (interior side only). For details refer to ESR Report 4373.



2-HR WALL PANEL

The code-compliant ProWood FR V343 2-hour wall assembly is manufactured under the independent third-party inspection of Underwriters Laboratories Inc. (UL), the largest and oldest independent testing laboratory in the United States. This wall assembly meets the highest available standard, carrying UL's FR-S designation, and is fully code compliant.









