















Treatment Standard	 <p>ABOVE GROUND/LIGHT DUTY Not suitable for deck joist or near ground uses UC3B</p>	 <p>GROUND CONTACT/GENERAL USE For general above ground, ground contact and fresh water use UC4A</p>	 <p>GROUND CONTACT/STRUCTURAL USE For critical structural, ground contact and fresh water use UC4B</p>
Not typically in contact with ground	  <p>Balusters & Railings Decking*</p>	    <p>Beams Joists Ledger Decking*</p>	
Typically in contact with ground		  <p>Stringers Posts*</p>	 <p>Posts*</p>
Reasons to choose treatment standard	<p>If ALL of the following apply:</p> <ul style="list-style-type: none"> ▪ Light Duty projects or functions ▪ Easily replaced or maintained ▪ Not critical to the integrity of the structure ▪ Above 6 inches from the ground ▪ Proper ventilation 	<p>If ANY of the following apply:</p> <ul style="list-style-type: none"> ▪ General Duty projects or functions ▪ Difficult to replace or maintain ▪ Critical to the integrity of the structure ▪ Less than 6 inches from the ground or touching the ground ▪ Inadequate ventilation ▪ Exposure to frequent or prolonged moisture or vegetation 	<p>If ANY of the following apply:</p> <ul style="list-style-type: none"> ▪ Heavy Duty projects or functions ▪ Difficult to replace or maintain ▪ Supporting a permanent structure ▪ Exposure to salt water ▪ Extreme / Tropical climates ▪ Supporting a dock, pier or marine structure

ProWood recommends at least Ground Contact (UC4A) treatment for any project.

*For decking and posts it is especially important to note where and how the component is being used in your project. For more information and technical specifications please visit ProWoodLumber.com/use.